## **GP15000E**



# GP SERIES Commercial/Residential Portable Generators

A/C Rated Output Watts 15,000

A/C Maximum Output Watts 22,500

#### **Model 5734**

UPC Number: 696471057348 Emissions Certification: 49-State



#### features

- GENERAC OHVI ENGINE, FULL PRESSURE LUBRICATION
- HIGH PERFORMANCE ALTERNATOR
- LARGE CAPACITY FUEL TANK FOR EXTENDED RUN TIME
- IDLE CONTROL
- CIRCUIT BREAKER PROTECTED OUTLETS
- LIFTING EYE
- FIXED HANDLES
- 12.3" PNEUMATIC WHEELS
- 1.25" HARDENED STEEL TUBE CRADLE
- LOW TONE MUFFLER

#### customer connections

#### Outlets


A	(1) Duplex 5-20R GFCI	
В	(1) Duplex 5-20R 120V	
C	(2) L5-30R	
n	(1) I 1 ( 20D	


D (1) L14-30R E (1) 12VDC F (1) 14-50R

#### **Circuit Breakers**

M	(2) 20A	
N	(4) 30A	
0	(1) 50A	

#### **Other Features**





### **GP15000E**

## specifications

	Product Series	GP15000E
	Model	5734
	Configuration/Emissions	49-State
	A/C Rated Output Watts:	15,000
	A/C Maximum Output Watts:	22,500
	A/C Voltage	120/240VAC
ĺ	A/C Frequency	60 Hz
	Rated 120/240 VAC Amperage	62.5
	Max 120/240 VAC Amperage	93.8
	Neutrals	Not bonded to ground (Floating)
	Engine Displacement	992cc
	Engine Type	OHVI
	Engine RPM	3600
	Recommended Oil	SAE 30
	Lubrication Method	Full Pressure
	Choke Type	Manual Lever
	Fuel Shut Off	Manual Lever
	Idle Control	Yes
	Starting Method	Electric
	Battery	Included
	Battery Size	12VDC 365 CCA
	Low Oil Shutdown Method	Low Pressure

Start Switch Type	3-Position
Switch Location	On Engine
Single-Point Lifting Eye	Yes
Fuel Gauge	Built-in Tank
Fuel Tank Capacity (Gal)	16
Fuel Tank Capacity (Ltrs)	60.56
Run Time at 50% (Hours)	10
Cord Set	N/A
Handle Style	Fixed
Wheel type	12.3" Pneumatic Wheels
Maintenance Kit	Included
Warranty - Residential	2 Year
Warranty - Commercial	1 Year

## dimensions and weights

Length (L)	48.5
Width (W)	31
Height (H)	39.5
Carton Length	49.25
Carton Width	23.25
Carton Height	31
Unit Weight (lbs)	363
Shipping Weight (lbs)	425

